

GE Series German Type Quick Coupling








Ordering code



Plug profile

S: Carbon steel

SS: Stainless steel SUS304/303



Compatible with

FOKCA	EU20
PARKER-RECTUS	25,26
JWL	520,530
CEJN	320

Features


GE20 series German type quick couplings can be interchanged with EU20 series, Parker-Rectus 25, 26, CEJN320 series. Like EU20, the flow rate of GE20 series is much larger than other 1/4" body couplings too, and it is compatible with all EU20 series nipples or plugs. Usually the body and sleeve are made of brass with acid pickling, and designed with two locking bars inside instead of locking balls, There are four types to the couplers: female thread, male thread, hose barb tail and nut-lock type.

This series of coupling is thick, safe and reliable, easy to connect and disconnect, push-to-connect sleeve realizes one-handed operation, and the maximum working pressure is 2.0MPa. For regular GE20 seires, it is available for 1/4" flow rate body only. If a larger flow rate is required, we can also provide GE30 and GE40 series.

Specification

Series	GE20
Body Size(in.)	1/4"
Rated Pressure(MPa)	2.0MPa
Temperature Range	−10°C ~ +70°C
Locking Device	2 bars

Performance



Flow Rate in I/min

GE Series German Type Quick Coupling



Self sealing socket+Thru-type plug

Sockets/Couplers


Female Pipe Thread



Male Pipe Thread




Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
GE20-SM-02	1/4	1/4"NPT	39.6	21	24.5



Standard Hose Barb





Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
GE20-SH-1/4	1/4	1/4"	54	21	24.5

Push-Lok Hose barb



Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
GE20-SN-1/4	1/4	1/4"	41	21	24.5

