
BR series british type pneumatic quick coupling


Self sealing socket+Thru-type plug





Plug profile

SS: Stainless steel SUS304/303



Compatible with

FOKCA	BR20
PARKER-RECTUS	19
PCL	60

Features


BR20 series British manual-operated type quick couplings can be interchanged with PCL 60 series, Parker-Rectus 19 series. Compatible with all Packer 19 series ferrules. The body, sleeve, and nipples or plugs are usually made of carbon steel with zinc or nickel-plated. It is equipped with 4 stainless steel locking balls.

The couplers are mainly divided into three types: female thread, male thread, and hose barb tail. The body of BR20 series coupler and plug has a long stem, not easy to come off. Manual operation is very simple, safe and reliable, The maximum working pressure is 2.0MPa. At present, the available body size is 1/4" only. If you need a larger flow rate, it is recommended to choose IN30, IN40, series.

Specification

Series	BR20
Body Size(in.)	1/4"
Rated Pressure(MPa)	2.0MPa
Temperature Range	-10°C ~ +70°C
Locking Device	4 balls

Performance



BR series british type pneumatic quick coupling




Self sealing socket+Thru-type plug



Sockets/Couplers

Female Pipe Thread





Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
BR20-SF-02	1/4	1/4"NPT	67.5	19	22.6

Male Pipe Thread




		-1
6 -		8

Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
BR20-SM-02	1/4	1/4"NPT	67.5	19	22.6

Standard Hose Barb






Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
BR20-SH-1/4	1/4	1/4"	86	19	22.6

Plugs/Nipples

Female Pipe Thread




Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
BR20-PF-02	1/4	1/4"NPT	50	16	




Male Pipe Thread





Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
BR20-PM-02	1/4	1/4"NPT	48.5	14	

Standard Hose Barb



Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
BR20-PH-1/4	1/4	1/4"	68	14	