

IS Series Israel Type Pneumatic Quick Coupling






Ordering code



Plug profile

S: Carbon steel

SS: Stainless steel SUS304/303



Compatible with

FOKCA IS20 PARKER-RECTUS CEJN

Features


IS20 series Israel manual-operated quick couplings have only 1/4" body size currently. Normally, the body, sleeve and plugs are made of carbon steel with white zinc plated. It is equipped with 4 stainless steel locking steel balls. The couplers are mainly divided into three types: female thread and male thread and hose barb tail.

Please note: The profile of IS20 series nipples is very close to that of IN20 series. They COULD NOT match with each other. For regular IS20 series couplers, the sealing material is NBR. if needs to use in a high temperature, it is recommended to replace its sealing with FKM(viton).


Specification

Series	BR20
Body Size(in.)	1/4"
Rated Pressure(MPa)	2.0MPa
Temperature Range	−10°C ~ +70°C
Locking Device	4 balls

Performance



IS Series Israel Type Pneumatic Quick Coupling



Self sealing socket+Thru-type plug




Sockets/Couplers

Female Pipe Thread




Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
IS20-SF-02	1/4	1/4"NPT	65	19	25.3



Male Pipe Thread




Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
IS20-SM-02	1/4	1/4"NPT	65	19	25.3



Standard Hose Barb




Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
IS20-SH-1/4	1/4	1/4"	75	19	25.3



Plugs/Nipples

Female Pipe Thread



Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
IS20-PF-02	1/4	1/4"NPT	47	16	

Male Pipe Thread



A
В

Model	Body Size	Thread -T	Overall (A)	Hex Size (B)	Diameter (D)
IS20-PM-02	1/4	1/4"NPT	46	14	

Standard Hose Barb



Model	Body Size	Hose I.D.	Overall (A)	Hex Size (B)	Diameter (D)
IS20-PH-1/4	1/4	1/4"	57	14	

